

HPS-04TQ II

4-Port 10M/100M PoE + 1-Port Gigabit Ethernet Managed Switch.



Key Features

- 1 x 10/100/1000 BaseT RJ45 ports
- Support 802.3at PoE supply
- Power isolation to ensure the equipment stability
- Working temperature: -20~60°C
- Plug& play with smart NVR series.
- Management functions

POWER OVER ETHERNET

Specifications

MODEL	HPS-04TQ II
Hardware Interface	
RJ45 Port	4 port 10/100BaseT with PSE 1 port 10/100/1000BaseT(X)
Led Indicator	Ethernet Link/Act PoE Status
Communications	
Standards	IEEE 802.3 10BaseT IEEE 802.3u 100BaseTX IEEE 802.ab 1000BaseT IEEE 802.3x Flow Control IEEE 802.3at Power Over Ethernet (PoE+) IEEE 802.3ad Link Aggregation Control Protocol IEEE 802.1p Class of Service IEEE 802.1Q VLAN
Transmission Data	10BaseT Cat. 3, 4, 5 UTP/STP 100BaseTX Cat. 5 UTP/STP 1000BaseT Cat. 5/5E,6 UTP/STP
Power	
Power Output	PoE 802.3at compliant 30W Max. per Port Total PoE power output capacity: 60W
Power Input	100~240V/AC, 50~60Hz
Network management	
Security	MAC Address Binding, TCP/UDP Filter
VLAN	802.1Q Tagged based, Port based
Traffic control	IGMP Snooping, Port Trunk, QoS/CoS (TCP/UDP port number, IP TOS/DS, 802.1p priority tag and physical port)
Environment	
Operating Temperature	-20 ~ 60°C
Humidity	0~80% RH (Non-condensing)
Dimension (W x H x D)	219 x 44 x 159 (mm).
Weight	1150g
Certification	CE & FCC

Made in Taiwan