

# VR04EP

4CH Plug & Play Full HD NVR POE 4Ch Plugs & Play Full HD NVR



#### **Key Features**

- \* ONVIF Compatible & Auto IP Camera Detection.
- \* Intelligent Dual (Main & Sub) Stream.
- \* PoE Switching HUB Built-in (upto 4 ch supported).
- Local Monitoring (HDMI/ VGA).
- \* Gigabit LAN/ uPNP.
- \* PUSH Notification to iPhone / iPad & Android Phone.
- Remote Monitoring by Remote S/W(CMS) & Smart Phone.
- \* Plug & Play with Built-in POE.

#### **NETWORK VIDEO RECORDER**

## **Specifications**

MODEL	VR04EP
System	
Operation System	Embedded Linux
Internal Storage	1 x SATA HDD
Video & Audio	
Protocol	Vision Hitech; Onvif
Video In	4CH (IP camera)
No. of PoE	4Ch (802.3af)
Video Out	HDMI, VGA, Composite
Display Speed	120fps
Audio In / Out	1CH / 1CH
Alarm In / Out	4CH / 1CH
Recording	
Recording Speed	120fps@1080p, 120fps@720p, 120fps@D1
Recording Mode	Continuous Schedule, Sensor, Motion, Pre&Post, Alarm,
_	Emergency Recording.
Playback	
Speed	x1, x2, x4, x8, x16, x32
Channel	1 / 4 ch split : Main stream
Search	Calendar (Date / Time) search, Event search
Backup Device	USB, Network Backup by CMS, File Backup to FTP.
Network	
LAN	Gigabit Ethernet (RJ45) - Fixed IP, DHCP & DDNS.
Advanced Function	1) Live Monitoring, Playback and File Backup on Remote 2) Time Synchronization by NTP Server ("pool.ntg.org") 3) Remote & E-Mail Notification, Remote System Reboot by IE, Remote PTZ Control.
Management	CMS & MMS (Smarteagle), Web (IE)
General	
System Recovery	Auto-Reboot and Journaling File System.
Advanced Function.	1) Import & Event of Setting Value, Water-Mark, AVI Backup
	2) HDD SMART Info
	3) Warning Alarm for System Over-Temperature
	4) Digital Zoom for both Live & VOD mode.
Power	48V x 2.5A D/C
Operating Temperature	5°C ~ 40°C / 20~90% RH
Dimension (W x D x H)	264 x 245 x 44 (mm), 1U
Certification	CE & FCC

### **Wire Diagram**

